

## Material Safety Data Sheet

### According to 91/155 EEC




Reviewed on 27.04.2005

#### 1 Identification of substance:

- **Product details:** Reagent for water analysis
- **Product name:** **COD-25 Cuvettes Low Range** (0-150 mg/l/ppm/COD/CSB)
- **Catalog number:** 251 990      **Model:** COD1 TC (LR)
- **Supplier:**  
 WTW Wissenschaftlich-Technische Werkstätten GmbH  
 Dr.-Karl-Slevogt-Straße 1  
 D-82362 Weilheim      Tel.: +49(0)881 183-0      Internet: <http://www.WTW.com>  
 Fax: +49(0)881 183-420      Tel.: +49(0)881 183-100      E-Mail: [Info@WTW.com](mailto:Info@WTW.com)
- **Emergency information:**  
 Poison Center Berlin, Germany  
 Tel.: +49(0)30 19240

#### 2 Composition/Data on components:

- **Description:** sulfuric acid solution
- **Dangerous components:**  
 The percent content of the mercury compound mentioned below refers to the amount of the pure mercury therein.

CAS: 7664-93-9 EINECS: 231-639-5 EC Number: 016-020-00-8	sulphuric acid	 C; R 35	80-90%
CAS: 7783-35-9 EINECS: 231-992-5 EC Number: 080-002-00-6	mercury sulphate	 T+,  N; R 26/27/28-33-50/53	0.1-1.0%

- **Additional information** For the wording of the listed risk phrases refer to section 16.

#### 3 Hazards identification

- **Hazard designation:**



T Toxic  
C Corrosive

- **Information pertaining to particular dangers for man and environment**

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

R 23/24/25 Toxic by inhalation, in contact with skin and if swallowed.

R 33 Danger of cumulative effects.

R 35 Causes severe burns.

R 52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

- **Classification system**

The classification is in line with current EC lists. It is expanded, however, by information from technical literature and by information furnished by supplier companies.

# Material Safety Data Sheet

## According to 91/155 EEC

Reviewed on 27.04.2005

Product name: **COD-25 Cuvettes Low Range****(0-150 mg/l/ppm/COD/CSB)**

(Contd. of page 1)

### 4 First aid measures

**· General information**

Personal protection for the First Aider!

Instantly remove any clothing soiled by the product.

Remove breathing apparatus only after soiled clothing has been completely removed.

In case of irregular breathing or respiratory arrest provide artificial respiration.

**· After inhalation**

Supply fresh air or oxygen; call for doctor.

In case of unconsciousness bring patient into stable side position for transport.

**· After skin contact**

Instantly rinse with water.

Instantly wash with polyethylene glycol 400.

Immediate medical treatment necessary. Failure to treat burns can prevent wounds from healing.

**· After eye contact**

Rinse opened eye for several minutes under running water.

Call a doctor immediately.

**· After swallowing**

Do not induce vomiting; instantly call for medical help.

Drink copious amounts of water and provide fresh air. Instantly call for doctor.

**· The following symptoms may occur:**

after inhalation:

damage to the affected mucous membranes

coughing

breathing difficulty

after swallowing:

metallic taste

bloody diarrhoea

pain

unconsciousness

Strong caustic effect.

**· Danger**

Danger of system failure.

Danger of gastric perforation.

**· Treatment**

If swallowed or in case of vomiting, danger of entering the lungs

Subsequent observation for pneumonia and pulmonary oedema

### 5 Fire fighting measures

**· Suitable extinguishing agents** CO<sub>2</sub>, sand, extinguishing powder. Do not use water.**· For safety reasons unsuitable extinguishing agents** Water.**· Special hazards caused by the material, its products of combustion or resulting gases:**

Development of hazardous combustion gases or vapours possible in the event of fire.

nitrous gases

Sulphur oxides (SO<sub>x</sub>)

mercury vapours

hydrogen

**· Protective equipment:**

Wear self-contained breathing apparatus.

Wear full protective suit.

**· Additional information**

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

Collect contaminated fire fighting water separately. It must not enter drains.

— GB —

(Contd. on page 3)

# Material Safety Data Sheet

## According to 91/155 EEC

Reviewed on 27.04.2005

**Product name: COD-25 Cuvettes Low Range (0-150 mg/l/ppm/COD/CSB)**

(Contd. of page 2)

### 6 Accidental release measures

- **Person-related safety precautions:**

Wear protective equipment. Keep unprotected persons away.  
Ensure adequate ventilation  
Use breathing protection against the effects of fumes/dust/aerosol.

- **Measures for environmental protection:**

Do not allow product to reach sewage system or water bodies.  
Inform respective authorities in case product reaches water or sewage system.

- **Measures for cleaning/collecting:**

Ensure adequate ventilation.  
Neutralize with diluted sodium hydroxide solution or by throwing on lime sand, lime or sodium carbonate.  
Absorb with liquid-binding material (sand, diatomite, universal binders).  
Dispose of contaminated material as waste according to item 13.

### 7 Handling and storage

- **Handling**

- **Information for safe handling:**

Ensure good ventilation/exhaustion at the workplace.  
Open and handle container with care.  
Prevent formation of aerosols.  
Work only in fume cupboard.

- **Information about protection against explosions and fires:**

Protect from heat.  
Keep breathing equipment ready.  
The product is not flammable

- **Storage**

- **Requirements to be met by storerooms and containers:** Store in cool location.
- **Information about storage in one common storage facility:** Store away from metals.
- **Further information about storage conditions:**  
Keep container tightly sealed.  
Store under dry conditions.  
Protect from humidity and keep away from water.  
This product is hygroscopic.  
Protect from the effects of light.
- **Storage class** Not required.

### 8 Exposure controls and personal protection

- **Additional information about design of technical systems:** No further data; see item 7.

- **Components with limit values that require monitoring at the workplace:**

**7783-35-9 mercury sulphate**

OES (Great Britain)	Long-term value: 0.025 mg/m <sup>3</sup> Bmgv
---------------------	--

- **Additional information:** The lists that were valid during the compilation were used as basis.

- **Personal protective equipment**

- **General protective and hygienic measures**

Keep away from foodstuffs, beverages and food.  
Take off immediately all contaminated clothing  
Wash hands during breaks and at the end of the work.  
Store protective clothing separately.  
Do not inhale gases / fumes / aerosols.  
Avoid contact with the eyes and skin.  
Do not eat, drink or smoke while working.

(Contd. on page 4)

# Material Safety Data Sheet

## According to 91/155 EEC

Reviewed on 27.04.2005

**Product name: COD-25 Cuvettes Low Range (0-150 mg/l/ppm/COD/CSB)**

(Contd. of page 3)

· **Breathing equipment:**

In case of brief exposure or low pollution use breathing filter apparatus. In case of intensive or longer exposure use breathing apparatus that is independent of circulating air.

· **Recommended filter device for short term use:** Filter P3

· **Protection of hands:**

Acid resistant gloves

Only use chemical-protective gloves with CE-labelling of category III.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Preventive skin protection by use of skin-protecting agents is recommended.

After use of gloves apply skin-cleaning agents and skin cosmetics.

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Butyl rubber, BR

Recommended thickness of the material:  $\geq 0.7$  mm

· **Penetration time of glove material**

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

Value for the permeation: Level  $\geq 6$  (480 min)

· **Eye protection:** Tightly sealed safety glasses.

· **Body protection:** Acid resistant protective clothing

### 9 Physical and chemical properties:

· <b>Form:</b>	Fluid
· <b>Colour:</b>	Yellow-brown
· <b>Odour:</b>	Recognizable
· <b>Melting point/Melting range:</b>	Not applicable
· <b>Boiling point/Boiling range:</b>	Not determined
· <b>Flash point:</b>	Not applicable
· <b>Self-inflammability:</b>	Product is not selfigniting.
· <b>Danger of explosion:</b>	Product is not explosive.
· <b>Density at 20°C</b>	1.76 g/cm <sup>3</sup>
· <b>Solubility in / Miscibility with Water:</b>	Fully miscible
· <b>pH-value at 20°C:</b>	~1
· <b>Solvent content:</b>	
<b>Organic solvents:</b>	0.0 %
<b>Water:</b>	< 20 %
· <b>Solids content:</b>	< 2 %

### 10 Stability and reactivity

· **Thermal decomposition / conditions to be avoided:** strong heating

· **Materials to be avoided:**

ammonia

alkali compounds

alkalis

acids

metals

halogen compounds

(Contd. on page 5)

# Material Safety Data Sheet

## According to 91/155 EEC

Reviewed on 27.04.2005

**Product name: COD-25 Cuvettes Low Range (0-150 mg/l/ppm/COD/CSB)**

(Contd. of page 4)

combustible substances

organic solvents

nitriles

peroxides

oxidizing agents

- **Dangerous reactions**

Corrosive action on metals

When diluting, always add acid to water, never vice versa

Reacts with metals forming hydrogen

---&gt; Explosive

Reacts with organic substances

Diluting or dissolving in water always causes rapid heating

- **Dangerous products of decomposition:**

nitrous gases

Sulphur oxides (SO<sub>x</sub>)

see chapter 5

## 11 Toxicological information

- **Acute toxicity:** Quantitative data on the toxicity of the preparation are not available.

- **LD/LC50 values that are relevant for classification:**

**7664-93-9 sulphuric acid**

Oral	LD50	2140 (25%) mg/kg (rat)
Inhalative	LC 50	510 (pure) mg/m <sup>3</sup> /2h (rat)

**7783-35-9 mercury sulphate**

Oral	LD50	57 mg/kg (rat)
Dermal	LD50	625 mg/kg (rat)

- **Primary irritant effect:**

- **on the skin:** Strong caustic effect on skin and mucous membranes.

- **on the eye:** Strong caustic effect.

- **Experience with humans:** Can cause kidney damages.

- **Additional toxicological information:**

The product shows the following dangers according to the calculation method of the General EC Classification Guidelines for Preparations as issued in the latest version:

Toxic

Corrosive

Danger by skin resorption.

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

Mercury compounds have a cytotoxic and protoplasmatoxic effect.

The principal signs manifest themselves in the CNS.

## 12 Ecological information:

- **Information about elimination (persistence and degradability):**

- **Other information:**

Quantitative data on the ecological effect of this product are not available.

Does not cause biological oxygen deficit.

- **Ecotoxic effects:**

- **Aquatic toxicity:**

The following applies to the water-soluble matter contained in inorganic Hg compounds in general:

The toxicity of mercury(II) ions for water organism depends on the water hardness (IPCS).

**7664-93-9 sulphuric acid**

Daphnia EC50	29 mg/l/24h (Daphnia magna)
--------------	-----------------------------

(Contd. on page 6)

# Material Safety Data Sheet

## According to 91/155 EEC

Reviewed on 27.04.2005

**Product name: COD-25 Cuvettes Low Range (0-150 mg/l/ppm/COD/CSB)**

(Contd. of page 5)

### 7783-35-9 mercury sulphate

EC50	0.005-3.6 mg/l/48h (Daphnia magna)
LC50	0.5 mg/l/48h (Leuciscus idus)
	0.19 mg/l/96h (Pimephales promelas)

· **Remark:**

Toxic for fish:  
sulphates > 7 g/l  
Forms corrosive mixtures with water even if diluted.

Harmful to aquatic organisms

· **Remark:** neutralization possible

· **General notes:**

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water.

Do not allow product to reach ground water, water bodies or sewage system.

Rinse off of bigger amounts into drains or the aquatic environment may lead to decreased pH-values. A low pH-value harms aquatic organisms.

## 13 Disposal considerations

· **Product:**

· **Recommendation**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Hand over to disposers of hazardous waste.

· **European waste catalogue**

16 05 07	discarded inorganic chemicals consisting of or containing dangerous substances
----------	--

· **Uncleaned packagings:**

· **Recommendation:** Disposal must be made according to official regulations.

· **Recommended cleaning agent:** Water, if necessary with cleaning agent.

## \*14 Transport information

**ADR/GGVSE: UN 3316 CHEMIE-TESTSATZ, 9, II**

**IMDG/GGVSee: UN 3316 CHEMICAL KIT, 9, II EMS Number: F-A S-P**

(Contd. on page 7)

# Material Safety Data Sheet

## According to 91/155 EEC

Reviewed on 27.04.2005

Product name: COD-25 Cuvettes Low Range)

(0-150 mg/l/ppm/COB/CSB)

(Contd. of page 6)

ICAO/IATA: CHEMICAL KIT, 9, UN 3316, II

### \* 15 Regulatory information

· **Designation according to EC guidelines:**

The product has been classified and labelled in accordance with EC Directives / Ordinance on Hazardous Materials (GefStoffV)

· **Code letter and hazard designation of product:**

T Toxic  
C Corrosive

· **Hazard-determining components of labelling:**

mercury sulphate  
sulphuric acid

· **Risk phrases:**

23/24/25 Toxic by inhalation, in contact with skin and if swallowed.  
33 Danger of cumulative effects.  
35 Causes severe burns.  
52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

· **Safety phrases:**

4 Keep away from living quarters.  
9 Keep container in a well-ventilated place.  
20 When using do not eat or drink.  
23 Do not breathe fumes/aerosol.  
26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.  
36/37/39 Wear suitable protective clothing, gloves and eye/face protection.  
45 In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).  
61 Avoid release to the environment. Refer to special instructions/safety data sheets.

· **Special designation of certain preparations:**

C

### 16 Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant R-phrases**

26/27/28 Very toxic by inhalation, in contact with skin and if swallowed.  
33 Danger of cumulative effects.  
35 Causes severe burns.  
50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

· **Department issuing data specification sheet:** Technical Department TSS, Dr. Manfred Kaul

· **\* Data compared to the previous version altered.**