

Material Safety Data Sheet

According to 91/155 EEC

Reviewed on 23.02.2005

Product name: Ntot1 TC (LR) LR Set 0-25 mg/l Part 1/2 (Total N Acid LR/HR mg/l; ppm)

(Contd. of page 1)

- **After eye contact**
Rinse opened eye for several minutes under running water.
Call a doctor immediately.
 - **After swallowing**
Rinse out mouth and then drink plenty of water.
Do not induce vomiting; instantly call for medical help.
 - **The following symptoms may occur:**
after inhalation:
damage to the affected mucous membranes
coughing
breathing difficulty
after swallowing:
cramps
diarrhoea
pain
sickness
vomiting
 - **Danger**
Danger of impaired breathing.
Danger of gastric perforation.
 - **Treatment**
If swallowed or in case of vomiting, danger of entering the lungs
Subsequent observation for pneumonia and pulmonary oedema
-

* 5 Fire fighting measures

- **Suitable extinguishing agents** CO₂, sand, extinguishing powder. Do not use water.
 - **For safety reasons unsuitable extinguishing agents** Water.
 - **Special hazards caused by the material, its products of combustion or resulting gases:**
Development of hazardous combustion gases or vapours possible in the event of fire.
nitrous gases
Sulphur oxides (SO_x)
hydrogen
 - **Protective equipment:**
Wear self-contained breathing apparatus.
Wear full protective suit.
 - **Additional information**
Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.
Collect contaminated fire fighting water separately. It must not enter drains.
-

* 6 Accidental release measures

- **Person-related safety precautions:**
Wear protective equipment. Keep unprotected persons away.
Ensure adequate ventilation
 - **Measures for environmental protection:** Do not allow product to reach sewage system or water bodies.
 - **Measures for cleaning/collecting:**
Neutralize with diluted sodium hydroxide solution or by throwing on lime sand, lime or sodium carbonate.
Absorb with liquid-binding material (sand, diatomite, universal binders).
Dispose of contaminated material as waste according to item 13.
Ensure adequate ventilation.
-

— GB —
(Contd. on page 3)

Material Safety Data Sheet

According to 91/155 EEC

Reviewed on 23.02.2005

Product name: Ntot1 TC (LR) LR Set 0-25 mg/l Part 1/2 (Total N Acid LR/HR mg/l; ppm)

(Contd. of page 2)

* 7 Handling and storage

- **Handling**
- **Information for safe handling:**
 - Prevent formation of aerosols.
 - Open and handle container with care.
- **Information about protection against explosions and fires:**
 - Protect from heat.
 - The product is not flammable
- **Storage**
- **Requirements to be met by storerooms and containers:** Store in cool location.
- **Information about storage in one common storage facility:**
 - Store away from water.
 - Store away from metals.
- **Further information about storage conditions:**
 - Keep container tightly sealed.
 - Store under dry conditions.
 - This product is hygroscopic.
- **Storage class** Not required.

* 8 Exposure controls and personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Components with limit values that require monitoring at the workplace:**
 - The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.
- **Additional information:** The lists that were valid during the compilation were used as basis.
- **Personal protective equipment**
- **General protective and hygienic measures**
 - Keep away from foodstuffs, beverages and food.
 - Take off immediately all contaminated clothing
 - Wash hands during breaks and at the end of the work.
 - Do not inhale gases / fumes / aerosols.
 - Avoid contact with the eyes and skin.
 - Do not eat, drink or smoke while working.
- **Breathing equipment:**
 - In case of brief exposure or low pollution use breathing filter apparatus. In case of intensive or longer exposure use breathing apparatus that is independent of circulating air.
- **Recommended filter device for short term use:** Filter B
- **Protection of hands:**
 - Acid resistant gloves
 - Only use chemical-protective gloves with CE-labelling of category III.
 - The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
 - Preventive skin protection by use of skin-protecting agents is recommended.
 - After use of gloves apply skin-cleaning agents and skin cosmetics.
- **Material of gloves**
 - The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
 - Butyl rubber, BR
 - Fluorocarbon rubber (Viton)
 - Recommended thickness of the material: ≥ 0.7 mm
- **Penetration time of glove material**
 - The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.
 - Value for the permeation: Level ≥ 6 (480 min)
- **Eye protection:** Tightly sealed safety glasses.

(Contd. on page 4)

Material Safety Data Sheet

According to 91/155 EEC

Reviewed on 23.02.2005

Product name: Ntot1 TC (LR) LR Set 0-25 mg/l Part 1/2 (Total N Acid LR/HR mg/l; ppm)

(Contd. of page 3)

· **Body protection:** Acid resistant protective clothing

* 9 Physical and chemical properties:

· Form:	Fluid
· Colour:	Clear
· Odour:	Recognizable
· Melting point/Melting range:	Not determined
· Boiling point/Boiling range:	Not determined
· Flash point:	Not applicable
· Self-inflammability:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive.
· Density at 20°C	1.748 g/cm ³
· Solubility in / Miscibility with Water:	Fully miscible
· pH-value at 20°C:	< 1
· Solvent content:	
Organic solvents:	0.0 %
Water:	< 20 %

* 10 Stability and reactivity

- **Thermal decomposition / conditions to be avoided:** strong heating
- **Materials to be avoided:**
 - oxidizing agents
 - ammonia
 - alkali compounds
 - alkalis
 - acids
 - metals
 - halogen compounds
 - combustible substances
 - organic solvents
 - nitriles
 - peroxides
- **Dangerous reactions**
 - Heating occurs when water is added
 - Corrosive action on metals
 - When diluting, always add acid to water, never vice versa
 - Reacts with metals forming hydrogen
 - > Explosive
 - Reacts with organic substances
- **Dangerous products of decomposition:**
 - Hydrogen
 - nitrous gases
 - Sulphur oxides (SO_x)
 - see chapter 5

— GB —

(Contd. on page 5)

Material Safety Data Sheet

According to 91/155 EEC

Reviewed on 23.02.2005

Product name: Ntot1 TC (LR) LR Set 0-25 mg/l Part 1/2 (Total N Acid LR/HR mg/l; ppm)

(Contd. of page 4)

* 11 Toxicological information

· **Acute toxicity:** Quantitative data on the toxicity of the preparation are not available.

· **LD/LC50 values that are relevant for classification:**

7664-93-9 sulphuric acid

Oral	LD50	2140 (25%) mg/kg (rat)
Inhalative	LC 50	510 (pure) mg/m ³ /2h (rat)

· **Primary irritant effect:**

· **on the skin:** Strong caustic effect on skin and mucous membranes.

· **on the eye:** Strong caustic effect.

· **Sensitization:** No sensitizing effect known.

· **Additional toxicological information:**

The product shows the following dangers according to the calculation method of the General EC Classification Guidelines for Preparations as issued in the latest version:

Corrosive

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

* 12 Ecological information:

· **Information about elimination (persistence and degradability):**

· **Other information:**

Inorganic substance. Does not cause biological oxygen deficit.

Quantitative data on the ecological effect of this product are not available.

· **Ecotoxic effects:**

· **Aquatic toxicity:**

7664-93-9 sulphuric acid

Daphnia EC50	29 mg/l/24h (Daphnia magna)
--------------	-----------------------------

· **Remark:**

Forms corrosive mixtures with water even if diluted.

Toxic for algae

Toxic for fish:

· **Remark:** neutralization possible

· **General notes:**

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water.

Do not allow undiluted product or large quantities of it to reach ground water, water bodies or sewage system.

Must not reach sewage water or drainage ditch undiluted or unneutralized.

Rinse off of bigger amounts into drains or the aquatic environment may lead to decreased pH-values. A low pH-value harms aquatic organisms. In the dilution of the use-level the pH-value is considerably increased, so that after the use of the product the aqueous waste, emptied into drains, is only low water-dangerous.

* 13 Disposal considerations

· **Product:**

· **Recommendation** Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· **European waste catalogue**

16 05 07	discarded inorganic chemicals consisting of or containing dangerous substances
----------	--

· **Uncleaned packagings:**

· **Recommendation:** Disposal must be made according to official regulations.

· **Recommended cleaning agent:** Water, if necessary with cleaning agent.

— GB —
(Contd. on page 6)

Material Safety Data Sheet

According to 91/155 EEC

Reviewed on 23.02.2005

Product name: Ntot1 TC (LR) LR Set 0-25 mg/l Part 1/2 (Total N Acid LR/HR mg/l; ppm)

(Contd. of page 5)

* 14 Transport information

· ADR/GGVSE:	UN 3316 CHEMIE-TESTSATZ, 9,, II
· IMDG/GGVSee:	UN 3316 CHEMICAL KIT, 9, II
· EMS-Number:	F-A S-P
· ICAO/IATA:	CHEMICAL KIT, 9, UN 3316, II

* 15 Regulatory information

· **Designation according to EC guidelines:**

The product has been classified and labelled in accordance with EC Directives / Ordinance on Hazardous Materials (GefStoffV)

· **Code letter and hazard designation of product:**

C Corrosive

· **Hazard-determining components of labelling:**

sulphuric acid

· **Risk phrases:**

35 Causes severe burns.

· **Safety phrases:**

20 When using do not eat or drink.

23 Do not breathe fumes/aerosol.

25 Avoid contact with eyes.

26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

30 Never add water to this product.

36/37/39 Wear suitable protective clothing, gloves and eye/face protection.

45 In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

(Contd. on page 7)

Material Safety Data Sheet

According to 91/155 EEC

Reviewed on 23.02.2005

Product name: Ntot1 TC (LR) LR Set 0-25 mg/l Part 1/2 (Total N Acid LR/HR mg/l; ppm)

60 This material and its container must be disposed of as hazardous waste.

(Contd. of page 6)

16 Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant R-phrases**

35 Causes severe burns.

· **Department issuing data specification sheet:** Department TSS, Dr. Manfred Kaul

· **Data compared to the previous version altered.**

—GB—

Material Safety Data Sheet

According to 91/155 EEC

Reviewed on 23.02.2005

* 1 Identification of substance:

- **Product details:** Reagent for water analysis
- **Product name:** Ntot1 TC (LR) LR Set 0-25 mg/l Part 1/2 (Vario Total Nitrogen Reagent A)
- **Catalog number:** 251 995 **Model:** Ntot1 TC (LR)
- **Supplier:**
WTW Wissenschaftlich-Technische Werkstätten GmbH
Dr.-Karl-Slevogt-Straße 1
D-82362 Weilheim Tel.: +49(0)881 183-0 Internet: <http://www.WTW.com>
Fax: +49(0)881 183-420 Tel.: +49(0)881 183-100 E-Mail: Info@WTW.com
- **Emergency information:**
Poison Center Berlin, Germany
Tel.: +49(0)30 19240

2 Composition/Data on components:

- **Chemical characterization:**
- **CAS No. Designation:**
7681-57-4 disodium disulphite
- **Identification number(s):**
- **EINECS Number:** 231-673-0
- **EC Number:** 016-063-00-2

* 3 Hazards identification

- **Hazard designation:**



Xn Harmful

- **Information pertaining to particular dangers for man and environment**
R 22 Harmful if swallowed.
R 31 Contact with acids liberates toxic gas.
R 41 Risk of serious damage to eyes.

* 4 First aid measures

- **General information**
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- **After inhalation** Supply fresh air; consult doctor in case of symptoms.
- **After skin contact**
Instantly wash with water and soap and rinse thoroughly.
If skin irritation continues, consult a doctor.
- **After eye contact**
Rinse opened eye for several minutes under running water.
Call a doctor immediately.

(Contd. on page 2)

Material Safety Data Sheet

According to 91/155 EEC

Reviewed on 23.02.2005

Product name: Ntot1 TC (LR) LR Set 0-25 mg/l Part 1/2 (Vario Total Nitrogen Reagent A)

(Contd. of page 1)

· After swallowing

Drink copious amounts of water, induce vomiting.
Instantly call for doctor.

· The following symptoms may occur:

after swallowing:
irritation
allergic reactions
Profuse sweating
after inhalation:
coughing
mucous membrane irritation
breathing difficulty

*** 5 Fire fighting measures****· Suitable extinguishing agents**

CO₂, extinguishing powder or water jet. Fight larger fires with water jet or alcohol-resistant foam.
Use fire fighting measures that suit the environment.

· Special hazards caused by the material, its products of combustion or resulting gases:

Formation of toxic gases is possible during heating or in case of fire.
Sulphur oxides (SO_x)

· Protective equipment:

Wear full protective suit.
Wear self-contained breathing apparatus.

· Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.
Collect contaminated fire fighting water separately. It must not enter drains.

*** 6 Accidental release measures****· Person-related safety precautions:**

Put on breathing apparatus.
Wear protective equipment. Keep unprotected persons away.
Avoid causing dust.

· Measures for environmental protection: Do not allow product to reach sewage system or water bodies.**· Measures for cleaning/collecting:**

Collect mechanically.
Ensure adequate ventilation.
Dispose of contaminated material as waste according to item 13.

*** 7 Handling and storage****· Handling**

· Information for safe handling: No special measures required.
· Information about protection against explosions and fires: The product is not flammable

· Storage

· Requirements to be met by storerooms and containers: Store in cool location.

· Information about storage in one common storage facility:

Do not store together with acids.
Store away from oxidizing agents.

· Further information about storage conditions:

Store under dry conditions.
Protect from humidity and keep away from water.
Protect from the effects of light.

(Contd. on page 3)

Material Safety Data Sheet

According to 91/155 EEC

Reviewed on 23.02.2005

Product name: Ntot1 TC (LR) LR Set 0-25 mg/l Part 1/2

(Vario Total Nitrogen Reagent A)

(Contd. of page 2)

· Storage class Not required.

* 8 Exposure controls and personal protection

· **Additional information about design of technical systems:** No further data; see item 7.· **Components with limit values that require monitoring at the workplace:**

7681-57-4 disodium disulphite (90-100%)

OES | Long-term value: 5 mg/m³· **Additional information:** The lists that were valid during the compilation were used as basis.· **Personal protective equipment**· **General protective and hygienic measures**

Keep away from foodstuffs, beverages and food.

Take off immediately all contaminated clothing

Wash hands during breaks and at the end of the work.

Avoid contact with the eyes.

· **Breathing equipment:** Use breathing protection against the effects of fumes/dust/aerosol.· **Recommended filter device for short term use:** Filter P1· **Protection of hands:**

Only use chemical-protective gloves with CE-labelling of category III.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

After use of gloves apply skin-cleaning agents and skin cosmetics.

· **Material of gloves**

nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.11 mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

· **Penetration time of glove material**Value for the permeation: Level ≥ 6 (480 min)

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:** Tightly sealed safety glasses.· **Body protection:** Protective work clothing.

* 9 Physical and chemical properties:

· Form:	Powder
· Colour:	Colourless
· Odour:	Pungent
· Melting point/Melting range:	150°C
· Boiling point/Boiling range:	Not applicable
· Flash point:	Not applicable
· Inflammability (solid, gaseous)	Product is not inflammable.
· Danger of explosion:	Product is not explosive.
· Density at 20°C	1.48 g/cm ³
· Settled apparent density at 20°C	1100-1200 kg/m ³
· Solubility in / Miscibility with	
Water at 20°C:	650 g/l
· pH-value (50 g/l) at 20°C:	4.5
· Organic solvents:	0.0 %

(Contd. on page 4)

— GB —

Material Safety Data Sheet

According to 91/155 EEC

Reviewed on 23.02.2005

Product name: Ntot1 TC (LR) LR Set 0-25 mg/l Part 1/2 (Vario Total Nitrogen Reagent A)

(Contd. of page 3)

· Solids content:	100.0 %
--------------------------	---------

* 10 Stability and reactivity

- **Thermal decomposition / conditions to be avoided:** strong heating
- **Materials to be avoided:**
 - oxidizing agents
 - > forms heat
 - acids
- **Dangerous reactions** Contact with acids releases toxic gases
- **Dangerous products of decomposition:**
 - Carbon monoxide and carbon dioxide
 - Nitrogen oxides (NOx)
 - Sulphur oxides (SOx)

* 11 Toxicological information

· **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

7681-57-4 disodium disulphite

Oral	LD50	1540 mg/kg (rat)
------	------	------------------

· **Primary irritant effect:**

- **on the skin:** No irritant effect.
- **on the eye:** Strong irritant with the danger of severe eye injury.
- **Sensitization:** No sensitizing effect known.

* 12 Ecological information:

- **Information about elimination (persistence and degradability):**
- **Other information:** Methods for the determination of biodegradability are not applicable to inorganic substances.
- **Ecotoxic effects:**

· **Acquatic toxicity:**

7681-57-4 disodium disulphite

EC50	89 mg/l/48h (Daphnia magna)
------	-----------------------------

LC50	150-220 mg/l/96h (Onchorhynchus mykiss)
------	---

· **Additional ecological information:**

· **CSB-value:**

7681-57-4 disodium disulphite

COD	0.168 g/g (.)
-----	---------------

· **General notes:**

- Harmful to aquatic organisms
- Water hazard class 1 (German Regulation) (Assessment by list): slightly hazardous for water.
- Do not allow undiluted product or large quantities of it to reach ground water, water bodies or sewage system.
- Must not reach sewage water or drainage ditch undiluted or unneutralized.

* 13 Disposal considerations

- **Product:**
- **Recommendation** Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 5)

Material Safety Data Sheet

According to 91/155 EEC

Reviewed on 23.02.2005

Product name: Ntot1 TC (LR) LR Set 0-25 mg/l Part 1/2 (Vario Total Nitrogen Reagent A)

(Contd. of page 4)

· **European waste catalogue**

16 05 07	discarded inorganic chemicals consisting of or containing dangerous substances
----------	--

- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.
- **Recommended cleaning agent:** Water, if necessary with cleaning agent.

* 14 Transport information

- **Land transport ADR/RID (cross-border)**
- **ADR/RID-GGVS/E Class:** -
- **Maritime transport IMDG:**
- **Marine pollutant:** No
- **Transport/Additional information:** Not dangerous according to the above specifications.

* 15 Regulatory information

- **Designation according to EC guidelines:**
The product has been classified and labelled in accordance with EC Directives / Ordinance on Hazardous Materials (GefStoffV)
- **Code letter and hazard designation of product:**
Xn Harmful
- **Risk phrases:**
22 Harmful if swallowed.
31 Contact with acids liberates toxic gas.
41 Risk of serious damage to eyes.
- **Safety phrases:**
2 Keep out of the reach of children.
26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
39 Wear eye/face protection.
46 If swallowed, seek medical advice immediately and show this container or label.

16 Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing data specification sheet:** Department TSS, Dr. Manfred Kaul
- **Data compared to the previous version altered.**

— GB —

Material Safety Data Sheet

According to 91/155 EEC

Reviewed on 23.02.2005

* 1 Identification of substance:

- **Product details:** Reagent for water analysis
- **Product name:** Ntot1 TC (LR) LR Set 0-25 mg/l Part 1/2 (Vario Total Nitrogen Reagent B)
- **Catalog number:** 251 995 **Model:** Ntot1 TC (LR)
- **Supplier:**
WTW Wissenschaftlich-Technische Werkstätten GmbH
Dr.-Karl-Slevogt-Straße 1
D-82362 Weilheim Tel.: +49(0)881 183-0 Internet: <http://www.WTW.com>
Fax: +49(0)881 183-420 Tel.: +49(0)881 183-100 E-Mail: Info@WTW.com
- **Emergency information:**
Poison Center Berlin, Germany
Tel.: +49(0)30 19240

2 Composition/Data on components:

- **Description:** Mixture of the substances listed below with harmless additions.


- **Dangerous components:**

CAS: 7681-57-4	disodium disulphite	✗ Xn; R 22-31-41	5-10%
EINECS: 231-673-0			
EC Number: 016-063-00-2			

- **Additional information** For the wording of the listed risk phrases refer to section 16.

3 Hazards identification

- **Hazard designation:**



Xi Irritant

- **Information pertaining to particular dangers for man and environment**

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

R 31 Contact with acids liberates toxic gas.

R 41 Risk of serious damage to eyes.

- **Classification system**

The classification is in line with current EC lists. It is expanded, however, by information from technical literature and by information furnished by supplier companies.

* 4 First aid measures

- **After inhalation** Supply fresh air; consult doctor in case of symptoms.
- **After skin contact**
Instantly rinse with water.
If skin irritation continues, consult a doctor.
- **After eye contact**
Rinse opened eye for several minutes under running water.

(Contd. on page 2)

Material Safety Data Sheet

According to 91/155 EEC

Reviewed on 23.02.2005

Product name: Ntot1 TC (LR) LR Set 0-25 mg/l Part 1/2 (Vario Total Nitrogen Reagent B)

(Contd. of page 1)

Call a doctor immediately.

· **After swallowing**

Rinse out mouth and then drink plenty of water.

Seek immediate medical advice.

· **The following symptoms may occur:**

after swallowing:

diarrhoea

irritation

allergic reactions

after inhalation:

coughing

mucous membrane irritation

breathing difficulty

* 5 Fire fighting measures

· **Suitable extinguishing agents**

CO₂, extinguishing powder or water jet. Fight larger fires with water jet or alcohol-resistant foam.

Use fire fighting measures that suit the environment.

· **Special hazards caused by the material, its products of combustion or resulting gases:**

Formation of toxic gases is possible during heating or in case of fire.

Sulphur oxides (SO_x)

· **Protective equipment:**

Wear self-contained breathing apparatus.

Wear full protective suit.

· **Additional information**

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

Collect contaminated fire fighting water separately. It must not enter drains.

* 6 Accidental release measures

· **Person-related safety precautions:**

Put on breathing apparatus.

Wear protective equipment. Keep unprotected persons away.

Avoid causing dust.

· **Measures for environmental protection:** Do not allow product to reach sewage system or water bodies.

· **Measures for cleaning/collecting:**

Collect mechanically.

Dispose of contaminated material as waste according to item 13.

* 7 Handling and storage

· **Handling**

· **Information for safe handling:** Ensure good ventilation/exhaustion at the workplace.

· **Information about protection against explosions and fires:**

Protect from heat.

The product is not flammable

· **Storage**

· **Requirements to be met by storerooms and containers:** Store in cool location.

· **Information about storage in one common storage facility:** Do not store together with acids.

· **Further information about storage conditions:** Store under dry conditions.

· **Storage class** Not required.

— GB —

(Contd. on page 3)

Material Safety Data Sheet

According to 91/155 EEC

Reviewed on 23.02.2005

Product name: Ntot1 TC (LR) LR Set 0-25 mg/l Part 1/2 (Vario Total Nitrogen Reagent B)

(Contd. of page 2)

* 8 Exposure controls and personal protection

· **Additional information about design of technical systems:** No further data; see item 7.

· **Components with limit values that require monitoring at the workplace:**

7681-57-4 disodium disulphite

OES (Great Britain) Long-term value: 5 mg/m³

· **Additional information:** The lists that were valid during the compilation were used as basis.

· **Personal protective equipment**

· **General protective and hygienic measures**

Take off immediately all contaminated clothing

Wash hands during breaks and at the end of the work.

Avoid contact with the eyes.

Do not eat, drink or smoke while working.

· **Breathing equipment:** Use breathing protection against the effects of fumes/dust/aerosol.

· **Recommended filter device for short term use:** Filter P1

· **Protection of hands:**

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Preventive skin protection by use of skin-protecting agents is recommended.

After use of gloves apply skin-cleaning agents and skin cosmetics.

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Nitrile

Recommended thickness of the material: ≥ 0.11 mm

· **Penetration time of glove material**

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

Value for the permeation: Level ≥ 6 (480 min)

· **Eye protection:** Tightly sealed safety glasses.

· **Body protection:** Protective work clothing.

* 9 Physical and chemical properties:

· Form:	Crystalline powder
· Colour:	Whitish
· Odour:	Odourless
· Melting point/Melting range:	Not determined
· Boiling point/Boiling range:	Not determined
· Flash point:	Not applicable
· Self-inflammability:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive.
· Density	Not determined
· Solubility in / Miscibility with Water:	Partly soluble
· pH-value:	Not determined
· Solvent content:	
Organic solvents:	0.0 %
· Solids content:	100.0 %

— GB —

(Contd. on page 4)

Material Safety Data Sheet

According to 91/155 EEC

Reviewed on 23.02.2005

Product name: Ntot1 TC (LR) LR Set 0-25 mg/l Part 1/2

(Vario Total Nitrogen Reagent B)

(Contd. of page 3)

* 10 Stability and reactivity

- **Thermal decomposition / conditions to be avoided:** strong heating
- **Materials to be avoided:**
 - oxidizing agents
 - > forms heat
 - acids
- **Dangerous reactions** Contact with acids releases toxic gases
- **Dangerous products of decomposition:**
 - Carbon monoxide and carbon dioxide
 - Nitrogen oxides (NOx)
 - Sulphur oxides (SOx)
 - see chapter 5

* 11 Toxicological information

- **Acute toxicity:** Quantitative data on the toxicity of the preparation are not available.

- **LD/LC50 values that are relevant for classification:**

57-13-6 urea		
Oral	LD50	8471 mg/kg (rat)
Dermal	LD50	8200 mg/kg (rat)
7681-57-4 disodium disulphite		
Oral	LD50	1540 mg/kg (rat)

- **Primary irritant effect:**
 - **on the skin:** No irritant effect.
 - **on the eye:** Strong irritant with the danger of severe eye injury.
- **Sensitization:** No sensitizing effect known.
- **Additional toxicological information:**

The product shows the following dangers according to the calculation method of the General EC Classification Guidelines for Preparations as issued in the latest version:

Irritant

* 12 Ecological information:

- **Information about elimination (persistence and degradability):**
- **Other information:** Quantitative data on the ecological effect of this product are not available.
- **Ecotoxicological effects:**

- **Acquatic toxicity:**

57-13-6 urea	
LC50	> 6810 mg/l/96h (Leuciscus idus)
7681-57-4 disodium disulphite	
EC50	89 mg/l/48h (Daphnia magna)
LC50	150-220 mg/l/96h (Onchorhynchus mykiss)

- **Additional ecological information:**

- **CSB-value:**

7681-57-4 disodium disulphite	
COD	0.168 g/g (.)

- **General notes:**

Water danger class 3 (German Regulation) (Self-assessment): extremely hazardous for water.
 Do not allow product to reach ground water, water bodies or sewage system, even in small quantities.
 Danger to drinking water if even extremely small quantities leak into soil.

Material Safety Data Sheet

According to 91/155 EEC

Reviewed on 23.02.2005

Product name: Ntot1 TC (LR) LR Set 0-25 mg/l Part 1/2

(Vario Total Nitrogen Reagent B)

(Contd. of page 4)

* 13 Disposal considerations

- **Product:**
- **Recommendation** Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

European waste catalogue	
16 05 06	laboratory chemicals, consisting of or containing dangerous substances, including mixtures of laboratory chemicals

- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.
- **Recommended cleaning agent:** Water, if necessary with cleaning agent.

14 Transport information

- | | |
|--|---|
| Land transport ADR/RID (cross-border) | |
| ADR/RID-GGVS/E Class: | - |

- | | |
|---------------------------------|----|
| Maritime transport IMDG: | |
| IMDG Class: | - |
| Marine pollutant: | No |

- | | |
|--|---|
| Air transport ICAO-TI and IATA-DGR: | |
| ICAO/IATA Class: | - |

- **Transport/Additional information:** Not dangerous according to the above specifications.

* 15 Regulatory information

- **Designation according to EC guidelines:**
The product has been classified and labelled in accordance with EC Directives / Ordinance on Hazardous Materials (GefStoffV)
- **Code letter and hazard designation of product:**
Xi Irritant
- **Risk phrases:**
31 Contact with acids liberates toxic gas.
41 Risk of serious damage to eyes.
- **Safety phrases:**
25 Avoid contact with eyes.
26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
39 Wear eye/face protection.
46 If swallowed, seek medical advice immediately and show this container or label.
56 Dispose of this material and its container to hazardous or special waste collection point.
60 This material and its container must be disposed of as hazardous waste.
64 If swallowed, rinse mouth with water (only if the person is conscious).

16 Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant R-phrases**
22 Harmful if swallowed.
31 Contact with acids liberates toxic gas.
41 Risk of serious damage to eyes.
- **Department issuing data specification sheet:** Department TSS, Dr. Manfred Kaul
- **Data compared to the previous version altered.**

Material Safety Data Sheet According to 91/155 EEC

Reviewed on 23.02.2005

* **1 Identification of substance:**

- **Product details:** Reagent for water analysis
- **Product name:** Ntot1 TC (LR) LR Set 0-25 mg/l Part 2/2 (Total N Hydroxide LR 0-25 mg/l; ppm)
- **Catalog number:** 251 995 **Model:** Ntot1 TC (LR)
- **Supplier:**
 WTW Wissenschaftlich-Technische Werkstätten GmbH
 Dr.-Karl-Slevogt-Straße 1
 D-82362 Weilheim Tel.: +49(0)881 183-0 Internet: <http://www.WTW.com>
 Fax: +49(0)881 183-420 Tel.: +49(0)881 183-100 E-Mail: Info@WTW.com
- **Emergency information:**
 Poison Center Berlin, Germany
 Tel: +49(0)30 19240

* **2 Composition/Data on components:**


- **Chemical characterization:** aqueous solution
- **Chemical characterization**

· Dangerous components:			
CAS: 1310-73-2	sodium hydroxide	C; R 35	0.1-1.0%
EINECS: 215-185-5			
EC Number: 011-002-00-6			

- **Additional information** For the wording of the listed risk phrases refer to section 16.

* **3 Hazards identification**

- **Hazard designation:**



Xi Irritant

- **Information pertaining to particular dangers for man and environment**
 The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.
 R 36/38 Irritating to eyes and skin.
- **Classification system**
 The classification is in line with current EC lists. It is expanded, however, by information from technical literature and by information furnished by supplier companies.

* **4 First aid measures**

- **General information** Instantly remove any clothing soiled by the product.
- **After inhalation** Supply fresh air and call for doctor for safety reasons.
- **After skin contact** Instantly wash with water and soap and rinse thoroughly.
- **After eye contact** Rinse opened eye for several minutes under running water. Then consult doctor.

(Contd. on page 2)

Material Safety Data Sheet

According to 91/155 EEC

Reviewed on 23.02.2005

Product name: Ntot1 TC (LR) LR Set 0-25 mg/l Part 2/2 (Total N Hydroxide LR 0-25 mg/l; ppm)

(Contd. of page 1)

- **After swallowing**
Rinse out mouth and then drink plenty of water.
Seek medical treatment.
- **The following symptoms may occur:**
after inhalation:
coughing
mucous membrane irritation
breathing difficulty
after swallowing:
sickness
irritation

* 5 Fire fighting measures

- **Suitable extinguishing agents** Use fire fighting measures that suit the environment.
- **Protective equipment:** Wear self-contained breathing apparatus.
- **Additional information**
Ambient fire may liberate hazardous vapours.
Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.
Collect contaminated fire fighting water separately. It must not enter drains.

* 6 Accidental release measures

- **Person-related safety precautions:** Wear protective equipment. Keep unprotected persons away.
- **Measures for environmental protection:** Do not allow product to reach sewage system or water bodies.
- **Measures for cleaning/collecting:**
neutralize with diluted sulphuric acid
Absorb with liquid-binding material (sand, diatomite, universal binders).
- **Additional information:** See Section 13 for information on disposal.

* 7 Handling and storage

- **Handling**
- **Information for safe handling:** Prevent formation of aerosols.
- **Information about protection against explosions and fires:**
Protect from heat.
The product is not flammable
- **Storage**
- **Requirements to be met by storerooms and containers:**
Unsuitable material for container: aluminium.
Store in cool location.
- **Further information about storage conditions:**
Keep container tightly sealed.
Store under dry conditions.
Protect from humidity and keep away from water.
Protect from the effects of light.
- **Storage class** Not required.

* 8 Exposure controls and personal protection

- **Additional information about design of technical systems:** No further data; see item 7.

(Contd. on page 3)

Material Safety Data Sheet

According to 91/155 EEC

Reviewed on 23.02.2005

Product name: Ntot1 TC (LR) LR Set 0-25 mg/l Part 2/2

(Total N Hydroxide LR 0-25 mg/l; ppm)

(Contd. of page 2)

· Components with limit values that require monitoring at the workplace:
1310-73-2 sodium hydroxide
OES (Great Britain) Short-term value: 2 mg/m³
· Additional information: The lists that were valid during the compilation were used as basis.

· Personal protective equipment
· General protective and hygienic measures

Keep away from foodstuffs, beverages and food.

Take off immediately all contaminated clothing

Wash hands during breaks and at the end of the work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

Do not eat, drink or smoke while working.

· Breathing equipment: Use breathing protection against the effects of fumes/dust/aerosol.

· Recommended filter device for short term use: Filter B

· Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Preventive skin protection by use of skin-protecting agents is recommended.

After use of gloves apply skin-cleaning agents and skin cosmetics.

· Material of gloves

Nitrile

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

Recommended thickness of the material: ≥ 0.11 mm
· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

Value for the permeation: Level ≥ 6 (480 min)
· Eye protection: Tightly sealed safety glasses.

· Body protection: Protective work clothing.

* 9 Physical and chemical properties:

· Form:	Fluid
· Colour:	Colourless
· Odour:	Odourless
· Melting point/Melting range:	Not determined
· Boiling point/Boiling range:	100°C
· Flash point:	Not applicable
· Danger of explosion:	Product is not explosive.
· Density at 20°C	1 g/cm ³
· Solubility in / Miscibility with Water:	Fully miscible
· pH-value at 20°C:	13
· Organic solvents:	0.0 %
· Water:	> 99 %

* 10 Stability and reactivity

· Thermal decomposition / conditions to be avoided: To avoid thermal decomposition do not overheat.

· Materials to be avoided:

acids

metals

(Contd. on page 4)

—GB—

Material Safety Data Sheet

According to 91/155 EEC

Reviewed on 23.02.2005

Product name: Ntot1 TC (LR) LR Set 0-25 mg/l Part 2/2

(Total N Hydroxide LR 0-25 mg/l; ppm)

(Contd. of page 3)

- **Dangerous reactions**
 - Corrosive action on metals
 - Corrodes aluminium
 - Reacts with metals forming hydrogen
 - > Explosive
- **Dangerous products of decomposition:** see chapter 5

* 11 Toxicological information

- **Acute toxicity:** Quantitative data on the toxicity of the preparation are not available.

- **LD/LC50 values that are relevant for classification:**

1310-73-2 sodium hydroxide

Oral	LD50	2000 mg/kg (rat)
------	------	------------------

- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Irritant effect.
- **Sensitization:** No sensitizing effect known.

* 12 Ecological information:

- **Information about elimination (persistence and degradability):**
- **Other information:**
 - Quantitative data on the ecological effect of this product are not available.
 - Does not cause biological oxygen deficit.
- **Ecotoxicological effects:**

- **Aquatic toxicity:**

1310-73-2 sodium hydroxide

LC 50	189 mg/l (fish)
-------	-----------------

- **Remark:** Forms corrosive mixtures with water even if diluted.
- **General notes:**
 - Rinse off of bigger amounts into drains or the aquatic environment may lead to increased pH-values. A high pH-value harms aquatic organisms.

* 13 Disposal considerations

- **Product:**
- **Recommendation** Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- **European waste catalogue**

16 05 07	discarded inorganic chemicals consisting of or containing dangerous substances
----------	--

- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.
- **Recommended cleaning agent:** Water, if necessary with cleaning agent.

— GB —
(Contd. on page 5)

Material Safety Data Sheet

According to 91/155 EEC

Reviewed on 23.02.2005

Product name: Ntot1 TC (LR) LR Set 0-25 mg/l Part 2/2 (Total N Hydroxide LR 0-25 mg/l; ppm)

(Contd. of page 4)

* 14 Transport information

· ADR/GGVSE: UN 3316 CHEMIE-TESTSATZ, 9, II

· IMDG/GGVSee: UN 3316 CHEMICAL KIT, 9, II
· EMS-Number: F-A S-P

· ICAO/IATA: CHEMICAL KIT, 9, UN 3316, II

* 15 Regulatory information

· **Designation according to EC guidelines:**

The product has been classified and labelled in accordance with EC Directives / Ordinance on Hazardous Materials (GefStoffV)

· **Code letter and hazard designation of product:**

Xi Irritant

· **Risk phrases:**

36/38 Irritating to eyes and skin.

· **Safety phrases:**

23 Do not breathe fumes/aerosol.

26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

37 Wear suitable gloves.

60 This material and its container must be disposed of as hazardous waste.

· **National regulations**

· **Water hazard class:** Generally not hazardous for water.

— GB —
(Contd. on page 6)

Material Safety Data Sheet

According to 91/155 EEC

Reviewed on 23.02.2005

Product name: Ntot1 TC (LR) LR Set 0-25 mg/l Part 2/2 (Total N Hydroxide LR 0-25 mg/l; ppm)

(Contd. of page 5)

16 Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant R-phrases**

35 Causes severe burns.

· **Department issuing data specification sheet:** Department TSS, Dr. Manfred Kaul

· **Data compared to the previous version altered.**

—GB—

Material Safety Data Sheet According to 91/155 EEC

Reviewed on 23.02.2005



* 1 Identification of substance:

- **Product details:** Reagent for water analysis
- **Product name:** Ntot1 TC (LR) LR Set 0-25 mg/l Part 2/2 (Vario Total N Persulfate RGT)
- **Catalog number:** 251 995 **Model:** Ntot1 TC (LR)
- **Supplier:**
 WTW Wissenschaftlich-Technische Werkstätten GmbH
 Dr.-Karl-Slevogt-Straße 1
 D-82362 Weilheim Tel.: +49(0)881 183-0 Internet: <http://www.WTW.com>
 Fax: +49(0)881 183-420 Tel.: +49(0)881 183-100 E-Mail: Info@WTW.com
- **Emergency information:**
 Poison Center Berlin, Germany
 Tel.: +49(0)30 19240

* 2 Composition/Data on components:

- **Description:** Mixture consisting of the following components.


- **Dangerous components:**

CAS: 7775-27-1 EINECS: 231-892-1	disodium peroxodisulphate	✘ Xn,  O; R 8-22-36/37/38-42/43	90-100%
CAS: 7727-21-1 EINECS: 231-781-8 EC Number: 016-061-00-1	potassium persulphate	✘ Xn,  O; R 8-22-36/37/38-42/43	5-10%

- **Additional information** For the wording of the listed risk phrases refer to section 16.

* 3 Hazards identification

- **Hazard designation:**



Xn Harmful
O Oxidising

- **Information pertaining to particular dangers for man and environment**

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

- R 8 Contact with combustible material may cause fire.
- R 22 Harmful if swallowed.
- R 36/37/38 Irritating to eyes, respiratory system and skin.
- R 42/43 May cause sensitisation by inhalation and skin contact.

- **Classification system**

The classification is in line with current EC lists. It is expanded, however, by information from technical literature and by information furnished by supplier companies.

Material Safety Data Sheet

According to 91/155 EEC

Reviewed on 23.02.2005

Product name: Ntot1 TC (LR) LR Set 0-25 mg/l Part 2/2 (Vario Total N Persulfate RGT)

(Contd. of page 1)

* 4 First aid measures

· General information

Instantly remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation

Supply fresh air or oxygen; call for doctor.

In case of unconsciousness bring patient into stable side position for transport.

· After skin contact

Instantly wash with water and soap and rinse thoroughly.

Seek medical treatment.

· After eye contact

Rinse opened eye for several minutes under running water.

Call a doctor immediately.

· After swallowing

Rinse out mouth and then drink plenty of water.

Call a doctor immediately.

· The following symptoms may occur:

after inhalation:

coughing

mucous membrane irritation

breathing difficulty

allergic reactions

after swallowing:

gastric or intestinal trouble

vomiting

irritation

· Danger

Danger of pulmonary oedema.

risk of airways sensitization

risk of skin sensitization

* 5 Fire fighting measures

· Suitable extinguishing agents

CO₂, extinguishing powder or water jet. Fight larger fires with water jet or alcohol-resistant foam.

Use fire fighting measures that suit the environment.

· Special hazards caused by the material, its products of combustion or resulting gases:

Formation of toxic gases is possible during heating or in case of fire.

Sulphur oxides (SO_x)

· Protective equipment:

Wear self-contained breathing apparatus.

Wear full protective suit.

· Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

Collect contaminated fire fighting water separately. It must not enter drains.

* 6 Accidental release measures

· Person-related safety precautions:

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Avoid causing dust.

Use breathing protection against the effects of fumes/dust/aerosol.

· Measures for environmental protection: Do not allow product to reach sewage system or water bodies.**· Measures for cleaning/collecting:**

Dispose of contaminated material as waste according to item 13.

(Contd. on page 3)

Material Safety Data Sheet

According to 91/155 EEC

Reviewed on 23.02.2005

Product name: Ntot1 TC (LR) LR Set 0-25 mg/l Part 2/2

(Vario Total N Persulfate RGT)

(Contd. of page 2)

Collect mechanically.
Ensure adequate ventilation.

* 7 Handling and storage

- **Handling**
- **Information for safe handling:** Work only in fume cupboard.
- **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect from heat.
Dust can combine with air to form an explosive mixture.
- **Storage**
- **Requirements to be met by storerooms and containers:** Store in cool location.
- **Information about storage in one common storage facility:** Store away from flammable substances.
- **Further information about storage conditions:**
Keep container tightly sealed.
Store under dry conditions.
Protect from humidity and keep away from water.
Protect from the effects of light.
- **Storage class** Not required.

* 8 Exposure controls and personal protection

- **Additional information about design of technical systems:** No further data; see item 7.

· Components with limit values that require monitoring at the workplace:

7775-27-1 disodium peroxodisulphate

OES (Great Britain)	Long-term value: 1 mg/m ³ measured as [S2O8]
---------------------	--

7727-21-1 potassium persulphate

OES (Great Britain)	Long-term value: 1 mg/m ³ measured as [S2O8]
---------------------	--

- **Additional information:** The lists that were valid during the compilation were used as basis.

· Personal protective equipment

· General protective and hygienic measures

Keep away from foodstuffs, beverages and food.
Take off immediately all contaminated clothing
Wash hands during breaks and at the end of the work.
Avoid contact with the eyes and skin.
Do not eat, drink or smoke while working.

- **Breathing equipment:** Use breathing protection against the effects of fumes/dust/aerosol.

- **Recommended filter device for short term use:** Filter P2

· Protection of hands:

Only use chemical-protective gloves with CE-labelling of category III.
After use of gloves apply skin-cleaning agents and skin cosmetics.

· Material of gloves

Nitrile

Natural rubber, NR

Recommended thickness of the material: ≥ 0.11 mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.
Value for the permeation: Level ≥ 6 (480 min)

(Contd. on page 4)

Material Safety Data Sheet

According to 91/155 EEC

Reviewed on 23.02.2005

Product name: Ntot1 TC (LR) LR Set 0-25 mg/l Part 2/2 (Vario Total N Persulfate RGT)

(Contd. of page 3)

- **Eye protection:** Tightly sealed safety glasses.
- **Body protection:** Protective work clothing.

* 9 Physical and chemical properties:

· Form:	Powder
· Colour:	White
· Odour:	Odourless
· Melting point/Melting range:	> 100°C
· Boiling point/Boiling range:	Not applicable
· Flash point:	Not applicable
· Inflammability (solid, gaseous)	Contact with combustible material may cause fire.
· Self-inflammability:	Product is not selfigniting.
· Density at 20°C	2.407 g/cm ³
· Solubility in / Miscibility with Water:	Soluble
· pH-value (25 g/l) at 20°C:	4.5
· Solvent content:	
Organic solvents:	0.0 %
· Solids content:	100.0 %

* 10 Stability and reactivity

- **Thermal decomposition / conditions to be avoided:** To avoid thermal decomposition do not overheat.
- **Materials to be avoided:**
 - combustible substances
 - alcohols
 - reducing agents
- **Dangerous reactions**
 - Can react violently with oxygen rich (oxidizing) material. Explosive.
 - Risk of dust explosion
- **Dangerous products of decomposition:**
 - Oxygen
 - (with water)
 - see chapter 5

* 11 Toxicological information

- **Acute toxicity:** Quantitative data on the toxicity of the preparation are not available.

· LD/LC50 values that are relevant for classification:		
7775-27-1 disodium peroxodisulphate		
Oral	LD50	930 mg/kg (rat)
7727-21-1 potassium persulphate		
Oral	LD50	802 mg/kg (rat)

- **Primary irritant effect:**
 - **on the skin:** Irritant to skin and mucous membranes.
 - **on the eye:** Irritant effect.

(Contd. on page 5)

Material Safety Data Sheet

According to 91/155 EEC

Reviewed on 23.02.2005

Product name: Ntot1 TC (LR) LR Set 0-25 mg/l Part 2/2

(Vario Total N Persulfate RGT)

(Contd. of page 4)

- **Sensitization:**

Sensitization possible by inhalation.

Sensitization possible by skin contact.

- **Subacute to chronic toxicity:**

CAS 7775-27-1:

MERCK: Sensitization test (guinea pig): positiv (OECD 406)

- **Additional toxicological information:**

The product shows the following dangers according to the calculation method of the General EC Classification Guidelines for Preparations as issued in the latest version:

Harmful

Irritant

* 12 Ecological information:

- **Information about elimination (persistence and degradability):**

- **Other information:**

Quantitative data on the ecological effect of this product are not available.

Methods for the determination of biodegradability are not applicable to inorganic substances.

- **Ecotoxic effects:**

- **Acquatic toxicity:**

7775-27-1 disodium peroxodisulphate

EC50 133 mg/l/48h (Daphnia magna)

LC50 771 mg/l/96h (Onchorhynchus mykiss)

7727-21-1 potassium persulphate

Daphnia EC50 357 mg/l/24h (Daphnia magna)

LC50 100 mg/l/96h (Poecilia reticulata)

- **Remark:**

lethal for fish:

sulphates > 7 g/l

Reacts with water to form toxic decomposition products.

- **General notes:**

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water.

Do not allow undiluted product or large quantities of it to reach ground water, water bodies or sewage system.

Must not reach sewage water or drainage ditch undiluted or unneutralized.

* 13 Disposal considerations

- **Product:**

- **Recommendation** Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- **European waste catalogue**

16 05 07 | discarded inorganic chemicals consisting of or containing dangerous substances

- **Uncleaned packagings:**

- **Recommendation:** Disposal must be made according to official regulations.

- **Recommended cleaning agent:** Water, if necessary with cleaning agent.

— GB —

(Contd. on page 6)

Material Safety Data Sheet

According to 91/155 EEC

Reviewed on 23.02.2005

Product name: Ntot1 TC (LR) LR Set 0-25 mg/l Part 2/2

(Vario Total N Persulfate RGT)

(Contd. of page 5)

* 14 Transport information

· ADR/GGVSE: UN 3316 CHEMIE-TESTSATZ, 9, II

· IMDG/GGVSee: UN 3316 CHEMICAL KIT, 9, II EMS Number: F-A S-P

· ICAO/IATA: CHEMICAL KIT, 9, UN 3316, II

* 15 Regulatory information

· **Designation according to EC guidelines:**

The product has been classified and labelled in accordance with EC Directives / Ordinance on Hazardous Materials (GefStoffV)

· **Code letter and hazard designation of product:**Xn Harmful
O Oxidising· **Hazard-determining components of labelling:**disodium peroxodisulphate
potassium persulphate· **Risk phrases:**8 Contact with combustible material may cause fire.
22 Harmful if swallowed.
36/37/38 Irritating to eyes, respiratory system and skin.
42/43 May cause sensitisation by inhalation and skin contact.· **Safety phrases:**17 Keep away from combustible material.
22 Do not breathe dust.

(Contd. on page 7)

Material Safety Data Sheet

According to 91/155 EEC

Reviewed on 23.02.2005

Product name: Ntot1 TC (LR) LR Set 0-25 mg/l Part 2/2 (Vario Total N Persulfate RGT)

(Contd. of page 6)

- 24 Avoid contact with skin.
 - 26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
 - 37 Wear suitable gloves.
 - 45 In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).
 - 60 This material and its container must be disposed of as hazardous waste.
-

16 Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant R-phrases**

- 22 Harmful if swallowed.
- 36/37/38 Irritating to eyes, respiratory system and skin.
- 42/43 May cause sensitisation by inhalation and skin contact.
- 8 Contact with combustible material may cause fire.

· **Department issuing data specification sheet:** Department TSS, Dr. Manfred Kaul

· **Data compared to the previous version altered.**

— GB —